



Be Right™



TU5200 Laboratory Laser Turbidimeter with RFID, EPA Version

Product #:

LPV442.99.03012

Web Price:

Rs.519,738.00

Ships within 6-8 weeks

The next standard in the evolution of turbidity

The TU5200 laboratory turbidimeter is part of Hach's TU5 series online and laboratory turbidimeters, designed specifically for the drinking water and other ultra pure water applications with an identical optic bloc in both the online and laboratory instruments.

The optical block of the turbidimeters was designed to let you see more of your sample than any other turbidimeter. The patented optical block features a 360° x 90° Detection Technology, with which the instrument measures turbidity not just from light reflected at a single point at 90° of the incident light, but rather from the full radius (360°) around the 90° from the incident light.

In this way, the TU5200 lab turbidimeter sees more of your sample than any other turbidimeter, delivering the best low level precision and sensitivity while minimizing variability from test to test. For the first time you will be able to remove the uncertainty of which measurement to trust, thanks to identical 360° x 90° Detection Technology in both the lab and online turbidity meters. With the TU5 turbidimeters, you can feel confident that you are in control of the turbidity in your drinking water plant.

Only the new TU5 Series Lab & Process Turbidimeters with 360° x 90° Detection deliver unprecedented confidence that a change in your reading is a change in your water.

Groundbreaking 360° x 90° Detection Technology

The TU5 Series employs a unique optical design that sees more of your sample than any other turbidimeter, delivering the best low level precision and sensitivity while minimising variability from test to test.

Matching lab and online results

For the first time you will be able to remove the uncertainty of which measurement to trust, thanks to identical 360° x 90° Detection Technology in both instruments.

Everything about turbidity – faster

The TU5 Series dramatically reduces the time needed to get a turbidity measurement you can rely on, with 98% less online sample surface area to clean, sealed vials for calibration, and the elimination of the need for indexing and silicone oil in the lab. Not to mention, a smaller online sample volume means you will detect events almost immediately.

Specifications

Accuracy:	±2% plus 0.01 NTU from 0 - 40 NTU; ±10% of reading from 40 - 1000 NTU based on Formazin primary standard (at 25 °C)
Calibration Method:	For Formazin and Stablcal: 20 NTU from 0 to 40 NTU; at 20 FNU and 600 NTU for full range
Custom calibration for up to 6-point calibrations	

Degrees 0 - 100 mg/L

SDVB 0 - 1000 NTU

CE compliant

US FDA accession number: 1420493-000 EPA version, 1420492-000 ISO version

Complies with IEC/EN 60825-1 and to 21 CFR 1040.10 in accordance with Laser Notice No. 50)

Australian ACMA Marking

Link2sc and RFID

195 mm x 409 mm x 278 mm

7" WVGA (800 x 480) colour TFT-LCD with touch screen

PC/ABS Blend Plastic

Communication:

Dimensions (H x W x D):

Display:

Enclosure Construction:

Light source:

Class 2 laser product, with embedded 650 nm (EPA 0.43 mW) or Class 1 laser product, with embedded 850 nm (ISO), max. 0.55 mW (complies with IEC/EN 60825-1 and to 21 CFR 1040.10 in accordance with Laser Notice No. 50)

Model:

TU5200 EPA

Operating Humidity:

80% at 30 °C (non condensing)

Operating temperature range:

10 - 40 °C

Power requirements (Hz):

50/60 Hz

Power requirements (Voltage):

100 - 240 VAC

Range:

EPA:

0 - 700 NTU / FNU / TE/F / FTU

0 - 100 mg/L

0 - 175 EBC

ISO:

0 - 1000 NTU / FNU / TE/F / FTU

0 - 100 mg/L

0 - 250 EBC

Regulatory:

EPA

Repeatability:

<40 NTU: Better than 1% of reading or ± 0.002 NTU on Formazin at 25 °C (77 °F), whichever is greater

>40 NTU: Better than 3.5% of reading on Formazin at 25 °C (77 °F)

0.0001 NTU / FNU / TE/F / FTU / EBC / mg/L

Resolution:

Signal averaging off: 7 seconds

Signal averaging on: 10 seconds (when averaging time is 5 seconds)

Sample Temperature:

4 - 70°C (39 - 158°F)

Source Lamp:

EPA Version - 650 nm Class 2 Laser

Storage conditions:

-30 to 60 °C (-22 to 140 °F)

Stray Light:

<10 mNTU

Units:

NTU, FNU, TE/F, FTU, EBC;

mg/L if calibrated with Degrees calibration curve

Warranty: 12 months

Weight: 2.4 kg

What's included?: TU5200 benchtop turbidimeter, user manual, Stablcal kit (10, 20 and 600 NTU), 2 sample vials, power supply, dust cover, vial stand

What's included?

TU5200 benchtop turbidimeter, user manual, Stablcal kit (10, 20 and 600 NTU), 2 sample vials, power supply, dust cover, vial stand